

# ABRAFLAT D /4

LAYFLAT CEMENT HOSE



## APPLICATION

Layflat delivery hose for concrete, sand, gravel and general abrasive dry materials

## TUBE

Black, smooth, **NR/SBR** conductive ( $R \leq 10^6$  Ohm) rubber compound

## REINFORCEMENT

High strength synthetic plies

## COVER

Black, smooth, antistatic cloth impression **SBR/NR** rubber compound, abrasion and weather resistant

## WORKING TEMPERATURE

-40°F +158°F

-40°C +70°C

## SPECIFICATIONS

ISO 4649  $70 \pm 5$  mm<sup>3</sup>

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
90	3 35/64	100	3 15/16	2.00	4	60	12	180	40/61
102	4	112	4 13/32	2.25	4	60	12	180	40/61
110	4 21/64	120	4 23/32	2.40	4	60	12	180	40/61
127	5	137	5 25/64	2.77	4	60	12	180	40/61
152	6	162	6 3/8	3.30	4	60	12	180	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

## BRANDING

