



# ABRASTAR /12 HD36

# SANDBLASTING HEAVY DUTY HOSE



# **APPLICATION**

Delivery hose, sand and bead blasting application, high pressure, high abrasion resistance

# **TUBE**

Black, smooth, NR/SBR antistatic rubber compound

#### REINFORCEMENT

High strength synthetic plies

#### **COVER**

Black, smooth, antistatic cloth impression  $\ensuremath{\mathbf{NR}/\mathbf{SBR}}$  rubber compound, abrasion and weather resistant

#### **WORKING TEMPERATURE**

-40°F +158°F

-40°C +70°C

#### **SPECIFICATIONS**

DIN 53516 36 ± 5 mm3

				WEIGHT	WP osi		<b>**</b>		2 2 2
mm	ID inch		0D nm inch				BP bar osi		COIL LENGTH m
19	3/4	33	1 19/64	0.71	12	180	36	540	40
25	1	40	1 37/64	0.96	12	180	36	540	40
32	1 1/4	48	1 57/64	1.26	12	180	36	540	40
38	1 1/2	56	2 13/64	1.44	12	180	36	540	40
38	1 1/2	60	2 23/64	1.48	12	180	36	540	40
51	2	71	2 51/64	2.39	12	180	36	540	40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

# BRANDING

