

AERSTEL /40

STEEL WIRE REINFORCEMENT COMPRESSED AIR HOSE



APPLICATION

Delivery hose for compressed air suitable for heavy duty and high pressure pneumatic tools in road constructions, railways works, tunneling and mining, etc

TUBE

Black, smooth, **SBR** rubber compound

REINFORCEMENT

High tensile strength steel reinforcements








COVER

Yellow, smooth, cloth impression **SBR** rubber compound, abrasion and weather resistant

WORKING TEMPERATURE

-22°F +176°F

-30°C +80°C

										
ID		OD		WEIGHT	WP		BP		BENDING RADIUS	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	m
13	1/2	22	7/8	0.41	40	600	160	2400	65	40/61
19	3/4	28	1 7/64	0.54	40	600	160	2400	95	40/61
25	1	34	1 11/32	0.69	40	600	160	2400	125	40/61
32	1 1/4	42	1 21/32	1.07	40	600	160	2400	160	40/61
38	1 1/2	48	1 57/64	1.27	40	600	160	2400	190	40/61
51	2	64	2 17/32	1.99	40	600	160	2400	255	40/61
63	2 1/2	77	3 5/16	2.43	30	450	120	1800	315	40/61
76	3	90	3 35/64	2.90	30	450	120	1800	380	40/61
102	4	116	4 9/16	4.10	30	450	120	1800	510	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

