

AGRASTEAM /170°C

FDA WASHDOWN HOSE



APPLICATION

Washdown hose for food industry floors and equipments

TUBE

White, smooth **EPR** rubber compound, food quality odourless and taste free

REINFORCEMENT

High strength synthetic plies

COVER

Blue, smooth, cloth impression **EPDM** rubber, resistant to abrasion, ozone and weather

WORKING TEMPERATURE

Hot water

-40°C +100°C / -40°F +212°F / WP 21 Bar

Steam

max +170°C / max +338°F / WP 7 Bar

Acqua calda

-40°C +100°C / PE 21 Bar

Vapore

max +170°C / PE 7 Bar

SPECIFICATIONS

FDA title 21 art.177.2600 (f) for fatty foods

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
13	1/2	24	61/64	0.42	7	105	70	1050	40
16	5/8	26	1 5/16	0.51	7	105	70	1050	40
19	3/4	31	1 7/32	0.65	7	105	70	1050	40
25	1	37	1 29/64	0.80	7	105	70	1050	40
32	1 1/4	46	1 13/16	1.00	7	105	70	1050	40
38	1 1/2	52	2 3/64	1.10	7	105	70	1050	40
51	2	65	2 9/16	1.60	7	105	70	1050	40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

