



AGRASTEAM D /170°C

FDA WASHDOWN HOSE



APPLICATION

Washdown hose for food industry floors and equipments

THRE

White, smooth EPR rubber compound, food quality odourless and taste free

REINFORCEMENT

High strength synthetic plies

COVER

Blue, smooth, cloth impression $\ensuremath{\mathbf{EPDM}}$ rubber, resistant to abrasion, ozone and weather

WORKING TEMPERATURE

Hot water

-40°C +100°C / -40°F +212°F / WP 21 Bar

Steam

max +170°C / max +338°F / WP 7 Bar

Acqua calda

-40°C +100°C / PE 21 Bar

Vapore

max +170°C / PE 7 Bar

SPECIFICATIONS

FDA title 21 art.177.2600 (f) for fatty foods

		8		4					21 22 23
ID		0D		WEIGHT	WP .		ВР		COIL LENGTH
13	1/2	24	inch 61/64	0.42	bar 7	psi 105	70	psi 1050	40
16	5/8	26	1 5/16	0.51	7	105	70	1050	40
19	3/4	31	1 7/32	0.65	7	105	70	1050	40
25	1	37	1 29/64	0.80	7	105	70	1050	40
32	1 1/4	46	1 13/16	1.00	7	105	70	1050	40
38	1 1/2	52	2 15/32	1.10	7	105	70	1050	40
51	2	64	2 17/32	1.60	7	105	70	1050	40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.



BRANDING

