

AQUAFLAT D /20

LAYFLAT WATER DELIVERY HOSE



APPLICATION

Layflat delivery hose for water, liquid fertilizer and non corrosive inert fluids for irrigation, submersible pumps and general industrial applications

TUBE

Black, smooth, **SBR** rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, cloth impression **SBR** rubber compound, abrasion and weather resistant

WORKING TEMPERATURE

-22°F +176°F

-30°C +80°C

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
60	2 3/8	69	2 23/32	1.30	20	300	60	900	20/40/61
70	2 3/4	79	3 7/64	1.57	20	300	60	900	20/40/61
76	3	86	3 25/64	1.77	20	300	60	900	20/40/61
80	3 5/32	91	3 37/64	1.99	20	300	60	900	20/40/61
90	3 35/64	102	4	2.15	20	300	60	900	20/40/61
102	4	113	4 29/64	2.51	20	300	60	900	20/40/61
110	4 21/64	122	4 51/64	2.63	20	300	60	900	20/40/61
120	4 23/32	131	5 5/32	2.93	20	300	60	900	20/40/61
127	5	139	5 15/32	3.15	20	300	60	900	20/40/61
152	6	163	6 27/64	3.67	20	300	60	900	20/40
203	8	219	8 5/8	5.75	20	300	60	900	20

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

