

# AQUARIG HW /35

SUCTION AND DELIVERY HOSE FOR POTABLE WATER



## APPLICATION

Suction and delivery hose for potable water on the oil rigs

## TUBE

White, smooth **BIIR** rubber compound food quality, odourless and taste free, manufactured on stainless steel mandrels

## REINFORCEMENT

High strength synthetic plies, with steel wire spirals and crossing copper wires for hose grounding

## COVER

Orange, smooth cloth impression, **EPDM** rubber compound, sea water and weather resistant

## WORKING TEMPERATURE

-40°F +212°F

-40°C +120°C

## SPECIFICATIONS

FDA title 21 art.177.2600 (e) for liquid foods, BfR, ADI free, PHTHALATE free, CE 1935/2004

ID		OD		WEIGHT	WP		BP		BENDING RADIUS	VACUUM	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	bar	m
51	2	71	2 51/64	2.91	35	525	105	1575	220	0.9	40
76	3	101	3 31/32	4.35	35	525	105	1575	350	0.9	40
102	4	132	5 13/64	6.40	35	525	105	1575	610	0.9	40
152	6	186	7 21/64	11.90	35	525	105	1575	900	0.9	40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

## BRANDING

