

CALORSTAR R /210°C ISO6134 2A

STEEL WIRE REINFORCEMENT STEAM HOSE 18 BAR - ISO 6134 -2A



APPLICATION

Delivery hose for high pressure saturated steam, suitable for tanks and pipelines steam cleaning in the petrochemical industry

TUBE

Black, smooth, EPM rubber compound

REINFORCEMENT

High tensile strength steel reinforcements

COVER

Red, smooth, pin pricked, cloth impression EPM rubber compound, abrasion, ozone and weather resistant

WORKING TEMPERATURE

-40°F +410°F peaks 450°F
-40°C +210°C picchi 232°C

SPECIFICATIONS

ISO 6134 - TYPE 2 CLASS A

ID		OD		WEIGHT	WP		BP		BENDING RADIUS	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	m
13	1/2	25	1	0.53	18	270	180	2700	120	40/61
16	5/8	30	1 3/16	0.75	18	270	180	2700	155	40/61
19	3/4	33	1 19/64	0.78	18	270	180	2700	185	40/61
25	1	40	1 37/64	1.02	18	270	180	2700	240	40/61
32	1 1/4	48	1 57/64	1.41	18	270	180	2700	330	40/61
38	1 1/2	54	2 1/8	1.77	18	270	180	2700	390	40/61
51	2	69	2 23/32	2.58	18	270	180	2700	520	40/61
63	2 1/2	81	3 3/16	3.16	18	270	180	2700	640	40/61
76	3	94	3 45/64	4.01	18	270	180	2700	745	40/61
102	4	122	4 51/64	6.21	18	270	180	2700	990	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

