

CALORSTEAM 170°C

TEXTILE REINFORCEMENT STEAM HOSE 7 BAR



APPLICATION

Delivery hose for low pressure saturated steam, suitable for tanks and pipelines steam cleaning in the petrochemical industry

TUBE

Black, smooth, EPM rubber compound

REINFORCEMENT

High strength synthetic plies







COVER

Black, smooth, cloth impression EPM rubber compound, abrasion, ozone and weather resistant

WORKING TEMPERATURE

-40°F +338°F

-40°C +170°C

									
ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
10	3/8	21	53/64	0.33	7	105	70	1050	40
13	1/2	24	61/64	0.37	7	105	70	1050	40
16	5/8	26	1 5/16	0.40	7	105	70	1050	40
16	5/8	28	1 7/64	0.42	7	105	70	1050	40
19	3/4	31	1 7/32	0.47	7	105	70	1050	40/61
25	1	37	1 29/64	0.58	7	105	70	1050	40/61
30	1 3/16	45	1 25/32	0.90	7	105	70	1050	40/61
32	1 1/4	44	1 47/64	0.90	7	105	70	1050	40/61
32	1 1/4	47	1 27/32	0.95	7	105	70	1050	40/61
38	1 1/2	52	2 15/32	1.10	7	105	70	1050	40/61
40	1 37/64	54	2 1/8	1.15	7	105	70	1050	40/61
51	2	67	2 41/64	1.70	7	105	70	1050	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

