

CALORSTEAM 170°C ISO 6134-1A

TEXTILE REINFORCEMENT STEAM HOSE ISO 6134-1A



APPLICATION

Delivery hose for low pressure saturated steam, suitable for tanks and pipelines steam cleaning in the petrochemical industry

TUBE

Black, smooth, EPM rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, cloth impression EPM rubber compound, abrasion, ozone and weather resistant







WORKING TEMPERATURE

-40°F +338°F

-40°C +170°C

SPECIFICATIONS

EN ISO 6134 TYPE 1 CLASS A

									
ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
13	1/2	25	1	0.43	6	90	60	900	40
16	5/8	30	1 3/16	0.60	6	90	60	900	40
19	3/4	33	1 19/64	0.66	6	90	60	900	40/61
25	1	40	1 37/64	0.90	6	90	60	900	40/61
32	1 1/4	48	1 57/64	1.11	6	90	60	900	40/61
38	1 1/2	54	2 1/8	1.27	6	90	60	900	40/61
51	2	69	2 23/32	1.89	6	90	60	900	40/61
63	2 1/2	81	3 3/16	2.23	6	90	60	900	40/61
76	3	94	3 45/64	2.76	6	90	60	900	40/61
102	4	122	4 51/64	4.02	6	90	60	900	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

