




CALORSTEAM /AL FDA 170°C

TEXTILE REINFORCEMENT STEAM HOSE 7 BAR - FDA



APPLICATION

Delivery hose for potable hot water mixed with steam and detergents. Mainly used for washdown and sterilization in the food industry workshops

TUBE

White, smooth, food quality EPM rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Blue, smooth, cloth impression $\ensuremath{\mathbf{EPDM}}$ rubber compound, abrasion, ozone and weather resistant

WORKING TEMPERATURE

-40°F +338°F

-40°C +170°C

SPECIFICATIONS

FDA title 21, art.177.2600 for aqueous foods

		8		4	WP				21 22 23
mm	ID inch	mm	D inch	WEIGHT kg/m	bar	P psi	bar	BP psi	COIL LENGTH m
10	13/32	20	25/32	0.28	7	105	70	1050	40
13	1/2	23	29/32	0.37	7	105	70	1050	40
15	19/32	25	1	0.41	7	105	70	1050	40
16	5/8	26	1 5/16	0.43	7	105	70	1050	40
19	3/4	31	1 7/32	0.58	7	105	70	1050	40
25	1	37	1 29/64	0.75	7	105	70	1050	40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

TGT CALORSTEAM	W.P. 7 BAR	FDA ITALY	tubi gomma torino	
W CALORSTEAN		W.P. F. BAR AL-PDA	··· ### ### ### ## ## ## ## ## ## ## ##	15tgt Italy