



CHEMIGEN /10

EPDM DELIVERY HOSE FOR CHEMICAL PRODUCTS



APPLICATION

Delivery hose for chemical products. Suitable for industrial water and water treatment plants. For deeper information, please check the chemical resistance table at the end of the catalog

TUBE

Black, smooth, EPDM antistatic rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, antistatic cloth impression $\ensuremath{\mathbf{EPDM}}$ rubber compound, resistant to chemical products, ozone and weather

WORKING TEMPERATURE

-40°F +212°F

-40°C +100°C

				4	± Ç ,		1 BP		21 22 23
mm	ID inch	mm Ol	inch	WEIGHT kg/m	bar	VP psi	bar	psi	COIL LENGTH m
13	1/2	23	29/32	0.38	10	150	30	450	40
19	3/4	29	1 9/64	0.44	10	150	30	450	40
20	25/32	30	1 3/16	0.46	10	150	30	450	40/60
25	1	35	1 3/8	0.55	10	150	30	450	40/60
30	1 3/16	42	1 21/32	0.85	10	150	30	450	40/60
32	1 1/4	44	1 47/64	0.88	10	150	30	450	40/60
35	1 3/8	47	1 27/32	1.05	10	150	30	450	40/60
38	1 1/2	52	2 15/32	1.21	10	150	30	450	40/60
40	1 37/64	55	2 11/64	1.41	10	150	30	450	40/60
51	2	66	2 19/32	1.81	10	150	30	450	40/60
60	2 23/64	76	3	2.08	10	150	30	450	40/60
80	3 5/32	96	3 25/32	2.77	10	150	30	450	40/60
102	4	118	4 41/64	3.60	10	150	30	450	40/60

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

