

MARINEGEN ISO7840 A1 L/L

FUEL DELIVERY HOSE FOR ON LEISURE BOATS- LONG LENGTH



APPLICATION

Delivery hose for diesel, bio diesel fuel and for eco gasoline, for marine engines installed on leisure boats (up to 24m)

TUBE

Black, smooth, **NBR** rubber compound

REINFORCEMENT

High strength synthetic plies

COVER

Black, smooth, **CR** rubber compound, self extinguishing, resistant to heat, fuels, and weather

WORKING TEMPERATURE

-4 °F +212 °F

-20 °C +100 °C

SPECIFICATIONS

ISO 7840:2004 A1 CE LL, approved RINA DIP 31503/DE/2, SAE J 1527:2004 A1

ID		OD		WEIGHT	WP		BP		COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	m
6	1/4	16	5/8	0.26	3.4	50	14	200	100
8	5/16	18	45/64	0.28	3.4	50	14	200	100
10	3/8	21	53/64	0.37	3.4	50	14	200	100
12	1/2	22	7/8	0.47	2.5	40	10	150	100
16	5/8	27	1 5/8	0.55	2.5	40	10	150	100
19	3/4	30	1 3/16	0.65	2.5	40	10	150	100

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

TGT MARINEGEN ISO 7840:2004 A1 CE L/L RINA DIP 31503/VE/2 SAE J 1527.2004 A1 ITALY