

PETROGALAXY SD /5

FUEL AND MINERAL OIL SUCTION AND DELIVERY HOSE - CORRUGATED



APPLICATION

Suction and delivery hose for mineral oils, diesel fuel and gasoline with aromatic contents up to 50%. Outstanding flexibility

TUBE

Black, smooth **NBR** rubber compound

REINFORCEMENT

High strength synthetic plies, with steel spirals and 1 copper wire for hose grounding








COVER

Black, convoluted, fire proof and antistatic, cloth impression **CR** rubber compound, resistant to oils, abrasion and weather

WORKING TEMPERATURE

-22°F +212°F

-30°C +100°C

									
mm	inch	kg/m	bar	psi	bar	psi	mm	bar	m
19	3/4	0.4	5	75	15	225	20	0.7	40
22	7/8	0.46	5	75	15	225	25	0.7	40
25	1	0.70	5	75	15	225	30	0.7	40
28	1 7/64	0.75	5	75	15	225	40	0.7	40
32	1 1/4	0.82	5	75	15	225	40	0.7	40
35	1 3/8	0.96	5	75	15	225	40	0.7	40
38	1 1/2	1.00	5	75	15	225	45	0.7	40
42	1 21/32	1.13	5	75	15	225	45	0.7	40
45	1 25/32	1.22	5	75	15	225	55	0.7	40
50	1 31/32	1.30	5	75	15	225	60	0.7	40
51	2	1.34	5	75	15	225	60	0.7	40
63.5	2 1/2	1.84	5	75	15	225	75	0.7	40
76	3	2.32	5	75	15	225	85	0.7	40
80	3 5/32	2.50	5	75	15	225	90	0.7	40
90	3 35/64	2.70	5	75	15	225	90	0.7	40
102	4	3.20	5	75	15	225	110	0.7	40

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

