

PETROSPIR SD/16 EN 1360 Type 2

FUEL AND MINERAL OIL SUCTION AND DELIVERY HOSE - EN 1360 TYPE 2



APPLICATION

Suction and delivery hose for fuels and petroleum derivatives with aromatic contents up to 50%

TUBE

Black, smooth, antistatic **NBR1** rubber compound

REINFORCEMENT

High strength synthetic plies, with steel spirals and 2 crossing copper wires for hose grounding

COVER

Black, smooth, fire proof and antistatic cloth impression **CR** rubber compound, resistant to chemical products, ozone and weather








WORKING TEMPERATURE

-22°F +158°F

-30°C +70°C

SPECIFICATIONS

EN 1360 TYPE 2 / TRbF

											
ID		OD		WEIGHT	WP		BP		BENDING RADIUS	VACUUM	COIL LENGTH
mm	inch	mm	inch	kg/m	bar	psi	bar	psi	mm	bar	m
19	3/4	30	1 3/16	0.62	16	240	48	720	100	0.9	40
25	1	38	1 1/2	0.93	16	240	48	720	150	0.9	40/61
32	1 1/4	45	1 25/32	1.18	16	240	48	720	175	0.9	40/61
35	1 3/8	48	1 57/64	1.27	16	240	48	720	190	0.9	40/61
38	1 1/2	51	2	1.45	16	240	48	720	225	0.9	40/61
40	1 37/64	54	2 1/8	1.66	16	240	48	720	230	0.9	40/61

Other diameters, pressure ratings are available on request. Technical data, structures and polymers are subject to change without notice.

BRANDING

